

# SAVOX

## SAVOX C-C550/TP2 Ex Remote Speaker Mic



Market Segment

Public Safety

Product code

L551252-11F1100

Size L

79 mm

Size W

37 mm

Size H

115 mm

Housing Material

Conductive Plastic

Housing Colour

Black

Weight (text)

170 g

Environmental Tests	Blowing Rain MIL810G 506.5, Procedure I, Blowing Sand MIL810G 510.5, Procedure II, Damp heat steady state MIL810G 507.5, Procedure I, Drop MIL810G 516.6, Procedure IV, Dust test MIL810G 510.5, Procedure I, Fluid contamination MIL810G 504.1, Procedure II (occasional contamination), High temperature (operational) MIL810G 502.5, Procedure II, A2, Immersion (IPx7) MIL810G 512.5, Procedure I, Mechanical Shock (Bump) MIL810G 516.6, Procedure I, Mechanical Shock MIL810G 516.6, Procedure I, Salt fog MIL810G 509.5, Solar radiation MIL810G 505.5, Procedure II A2, Thermal shock MIL810G 503.5, Procedure I-A, Vibration MIL810G 514.6, Procedure I, Category 24	Operational Temperature Min	-40 °C (-40 °F)
Operational Temperature Max	85 °C (185 °F)	Ingress Protection	IP66, IP67
Storage Temperature Min	-25 °C (-13 °F)	Storage Temperature Max	70 °C (158 °F)
Protection Against Drop(fall)	1 meter	RX audio SPL( XXdB; X,X W; X,X m)	98 +/-3dB/1W/0.3m
TX Audio, Microphone Sensitivity(XXdB +/-XdB)	-39dB +/-2dB	Microphone Type	Omnidirectional
Headset Connector	QR4+1 female	Connectivity	Wired
Cable Type	Coiled	Use Voltage	3.0...10.0VDC(0VDC for dynamic microphone)
Ex/IS	ATEX / IECEx	Emergency Button	Yes
Attachment/Fastening	Clothing Clip	Compatible Radio Links	Tait TP3461 IS, Tait TP9361 EX