SAVOX

VisionX-Server

- The perfect solution to lifecycle management
- Controlled generation changesSupported by fist class service
- Highly reliable
- Individually tested and quality controlled
- Available in two different models (Client / Server)

Market Segment	Public Safety	Product code	U000605
Size L	255 mm	Size W	163 mm
Size H	155 mm	Housing Material	Metal
Housing Colour	Black	Weight (text)	5 kg
Options (text)	Audio: Intel® C246 PCH-H built-in HD Audio+ALC888S-VD2-GR Watchdog Timer: 256 levels iAMT: 11.6	Operational Temperature Min	0 °C (32 °F)
Operational Temperature Max	55 °C (131 °F)	Ingress Protection	IP20
Storage Temperature Min	-20 °C (-4 °F)	Storage Temperature Max	80 °C (176 °F)
Type	Platform	Platform	Compact
CPU-card	MI998AF-C246 Mini-ITX Embedded Board	Chipset	Intel C246
CPU	8th/9th Generation Intel Xeon	CPU Socket	LGA1151
RAM Memory Type	DDR4 2666 MHz SO-DIMM	RAM Memory Max	32 GB
ECC Memory	Yes	Mass Storage	4 x 2.5", Shock Damping System
Display Interface	1 x DisplayPort, 1 x DVI-D, 1 x HDMI	Graphics Controller	Integrated, Intel UHD Graphics
LAN ports	2	LAN chip	1 x Intel I210-AT 1Gbps, 1 x Intel I219-LM 1Gbps
TMP	2.0	Digital I/O	4-in/4-out
SATA	4 x SATA III		

Savox Communications Oy Ab (Ltd)
Keilaranta 15 B
02150 Espoo, Finland

RAID	Intel RST Premium With Intel Optane System Acceleration (0, 1, 5, 10)	USB	1 x USB 2.0 (on board), 6 x USB 3.0
Serial Port	2 x RS-232 (on board), 2 x RS-232/422/485	Mini Type Slots	1 x M.2 (E-Key, type:2230, CNVi), 1 x M.2 (M-Key, type:2280, NVMe), 1 x SD Card
Card Slots	1 x PCIe (x16)	Operating System	Windows Server 2019
Power Supply	170W (18-36 VDC)	Cooling	Active (optional), Air filter, Passive
Mounting	Table, Wall		